

Features:

- Mains as well as 12VDC operation
- Coin Acceptor Activation
- Programmable to 6 different types of coins.
- 2.8 inch TFT Display and 5 programme keys and user interface
- Simple cursor selectable menu based settings
- All settings accessible only through a Password
- Auto Calibration
- Real Time Clock (RTC)
- Quantity per coin unit settable
- Dispensed Water totalised display
- Total record of volume dispensed and coin amount.
- Operation selectable in Batch and Timer modes
- Feed Tank level check
- Data transfer on GSM (Optional)

Specifications:

- Power : 100-270VAC
- Solenoid: 12VDC (Internal)
- Flow Sensor: Pulse Type
- Level Sensing: Treated Water Level Floaty
- Display: 2.8" TFT, Monochrome
- Programming Keys: 5
- Suitable for 6 different types of coins
- Size: 300H X350W X190 D mm
- Water Inlet Connection: $\frac{3}{4}$ " BSPM Union
- Water Outlet Connection: $\frac{3}{4}$ " Solvent Cementable.
- Water Column : 1 m (min)



PROTON POWER CONTROL PVT.LTD.
S.NO.28 JAGTAP DAIRY, PIMPLE NILAKH
PUNE-411027.
TEL: 020-27270800, 27276777.
TEL/FAX: 020-27270100.
MOBILE: 9764885010/9422009655.
E-MAIL: sales@protonpowercontrol.com